

MAXISTRADA SERIES

Modern design. Robust street light fitting.



Description
Features:

Model.: LT-YZDH739

Rating:IP65

Housing,door frame,spigot: Be made of die-casting aluminum with corrosion-resistant polyester powder coat finish.The door frame is connected to the rotating shaft at the end part of the housing with screws for preventing it from falling down when toolless loosen the stainless steel clip and open the housing for safe and easy maintenance.

Reflector:High pure aluminum reflector fixed to the housing provides accurate light distribution and high light efficiency.

Lampholder:Lampholder is adjustable up & down, forward & backward for getting various photometriccurves from the specific reflector.

Sealing gasket: Heat-resistant silicon gasket sealed around the glass and the door frame for ensuring high performance of protection against moisture and contaminant.

Aplication: Urban road, highways, railways, warehouse surroundings, condominiums, port, factory area etc.

Installation

Integrated with mounting screws for quick and easy tightening on \varnothing 48mm round pole for horizontal or vertical installation.Angle is adjustable.

Model	Dimension	Power	Capacitor	Light source	Lamp Type
	LxWxH(mm)				
LT-YZDH739	750 x 350 x 220	250W	18 μ F	SON-T / MHT-T	E40
LT-YZDH739	750 x 350 x 220	400W	25 μ F	SON-T / MHT-T	E40