

T5 MASTERLITE

T5 2x24/4x24/5x24w street light complete range series



Data:

Energy efficient roadway street light ,luminaire housing of deep draw aluminium sheet with specialy designed pre-anodised reflector and acrylic cover complete with all accessories suitatable for 2x24w,4x24w and 5x24w T5 MASTERLITE series

Description Features: Rating:IP65

Electrical Safety: Class I

- Powder coated Housing

- Pre-anodised, fixed on gear tray. Reflector - MS, white powder coated Gear

- Clear acrylic. Cover Toggles - MS, electroplated

Gasket - EPDM.

Internal wiring - PVC insulated copper wire.

Mains Terminal - 2 way 10 amps. suitable for terminating 1.5 sq. mm cable.


Hardware

MS,Zinc plated & passivated
1 No. suitable for 14 SWG earthing wire.
Wired with energy efficient electronic Earthing Ballast \

ballast.



Compact in shape and Uniform illumination Elegant and sleak in appearance Easy to install and maintain Fully weather-proof



Mounting system-suitable for 60mm O.D. mounting pipe.

Maintenance-acrylic cover can be opened for lamp replacement and gear tray for accessories maintenance.

Aplication: Major city roads, secondary roads, round abouts, industrial complaxes, Residential colonies, car parking, etc.

Model	Lamp Type	Voltage	App.Wt(Kg)	Current(A) at 240V	Power Factor	Dimension
LT ST 004 HFD4	4 x 24W-T5	240V	4.6	0.40	0.95 up	A610 x B375 x C162
LT ST 005 HFD4	5 x 24W-T5	240V	5.1	0.24	0.95 up	A610 x B375 x C162
LT ST 006 HFD2	2 x 24W-T5	240V	4.0	0.32	0.95 up	A610 x B375 x C162