

## **VERDURE SERIES**

Business area, condominium, gardens, square, walking street, park, residence community, etc.



Description Features:

Model - LTYZTH862

## Rating:IP65

Pole:Hot galvanized steel pole with top 060mm and corrossionresistant polyester powder coat finished.High performance of rigidity and corrossion resistance.

Housing,top cover: Housing,top cover:Die-casting aluminum housing and superior aluminum sheet moulded cover with corrossion-resistant polyester powder coat finish. Integrated four stainless steel screws for fixing with pole .Toolless unscrewing the plastic knob screws from the top cover for quick and easy maintenance.

Diffuser: UV-resistant polycarbonate diffuser provides uniform light distribution and free from glare

Aplication: Business district, square, walking street, park, residence community etc.

## Installation:

Traditional flange plate(250x250mm) available in the bottom of the pole with 4 standard bolt holes in and the hole-distance 200mm between each for fixing firmly.

	Model	Dimension	Power	Capacitor	Light source	Lamp Type	
		LxWxH(mm)					
	LTYZTH862	380 x 333 x 60	70W	12µF	SON-T / MHT-T	E27	
	LTYZTH862 Pole	2.5MT x 114 x 60	N.Aplicable	N.Aplicable	N.Aplicable	N.Aplicable	